## MIO BAS C

## MIOS Tap Range Mios Basin Mixer with Clicker Waste Chrome



|   |        | res:   |
|---|--------|--------|
| _ | $\sim$ | raci   |
|   | -c     | 11 – 5 |
|   |        |        |

- Everything you need in the box including flexible tails and clicker waste so nothing to buy separately.
- Long life ceramic cartridge for added durability and smooth control.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- Supplied with pre-fitted flow limiters to reduce water flow to 4.5I/min per spout
- 5 year parts and 1 year labour guarantee for peace of mind.

## **Product Certifications:**

**O** Water Label


**4.4** l/min


For more products, visit our website: http://www.bristan.com



| Specification                     |                                   |  |  |  |  |  |
|-----------------------------------|-----------------------------------|--|--|--|--|--|
| Product Type:                     | Bathroom Taps                     |  |  |  |  |  |
| Main Construction Material:       | Brass                             |  |  |  |  |  |
| Mount Type:                       | Deck                              |  |  |  |  |  |
| Handle Type:                      | Lever                             |  |  |  |  |  |
| Connection Inlet:                 | 1/2" BSP Flexible Tails           |  |  |  |  |  |
| Connection Outlet:                | M24 4.5lpm Flow Limited Aerator   |  |  |  |  |  |
| Number of Tap Holes:              | 1                                 |  |  |  |  |  |
| Valve/Cartridge Type:             | 35mm Single Lever Cartridge       |  |  |  |  |  |
| Plumbing System Requirements:     | Suitable for all plumbing systems |  |  |  |  |  |
| Minimum Dynamic Pressure (bar):   | 0.3 bar                           |  |  |  |  |  |
| Maximum Dynamic Pressure (bar):   | 5 bar                             |  |  |  |  |  |
| Maximum Hot Water Temperature °C: | 65°C                              |  |  |  |  |  |
| Maximum Static Pressure (bar):    | 10 bar                            |  |  |  |  |  |
| Flow Type:                        | Single                            |  |  |  |  |  |
| Isolation Included:               | No                                |  |  |  |  |  |
|                                   |                                   |  |  |  |  |  |

Dimensions (measurements in mm)





| Flow Rates (I/min)    |     |     |   |   |     |     |  |  |  |
|-----------------------|-----|-----|---|---|-----|-----|--|--|--|
| System Pressure (bar) | 0.3 | 0.5 | 1 | 2 | 3   | 5   |  |  |  |
| MIO BAS C (mixed)     | 1.6 | 2   | 3 | 4 | 4.4 | 4.4 |  |  |  |

## TECHNICAL DATA SHEET



